

REPSOL MXR MATIC PLATINUM



ACTION SERIES MOTORCYCLE

Lubricants

Description

Repsol MXR Matic Platinum is a ultra high quality engine oil for high performance 4T engines. It contains special additives that improve lubricity and maintain a low friction coefficient. These additives are also in accordance to the quality standards of JASO MB. It is recommended for use in motorcycles that require a low-friction lubricant. JASO MB is recommended especially for dry-clutch scooters and automatic-transmission motorcycles.

Properties

- Trials in four-stroke motorcycles under extreme working conditions have confirmed excellent protection against wear.
- Formula offers a high level of performance and, in turn, guarantees adequate friction reduction for the parts coated in the oil.
- Unique friction modifier additives facilitate fuel savings, keeping the engine protected.

Quality Levels

- API SN
- JASO T 903:2016 MB

Technical Specifications

	UNIT	METHOD	VALUE	
SAE Grade			10W30	10W40
Density a 15 °C	g/mL	ASTM D 4052	0.853	0.821
Viscosity at 100 °C	cSt	ASTM D 445	10.5	14.45
Viscosity at 40 °C	cSt	ASTM D 445	63	100
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.	-
Viscosity index	-	ASTM D 2270	147	160
Flash point, open cup	°C	ASTM D 92	242	244
Pour point	°C	ASTM D 97	-27	-24
T.B.N.	mg KOH/g	ASTM D 2896	8.0	8.0
Sulphated ashes	% in weight	ASTM D 874	0.7	0.7
Noak Volatility	% in weight	ASTM D 5800	10,7 min	7.7

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. March 2020.