REPSOL RSGEAR EP5 80W90 & 85W140



ACTION SERIES TRANSMISSIONS

Lubricants

Description

Repsol RSGear EP5 is a multigrade, extreme pressure lubricant oil suitable for vehicle differentials and hypoid and helical transmission units that require API GL-5 quality levels. This oil has been specially designed to comply with requirements set by the leading vehicle manufacturers. It performs outstandingly in extreme pressure conditions to provide the highest protection in heavy-load applications.

Properties

- Excellent capacity for withstanding peak loads and temperatures.
- Offers a better response to manual gearbox synchronisation than monograde oil, given its lower friction in gear cogs, particularly at low temperatures.
- Excellent anti-wear and anti-rust properties, prolonging the service life of the transmission.
- Very good resistance to ageing.

Quality Levels

• API GL-5

Technical Specifications

UNIT	METHOD	VALU	E
	SAE J300	80W90	85W140
g/ml	ASTM D 4052	0,890	0,903
cSt	ASTM D 445	14,5	26,2
cSt	ASTM D 445	147	363
cP	ASTM D 2983	< 150.000	
сP	ASTM D 2983		< 150.000
-	ASTM D 2270	101	98
٥C	ASTM D 92	230	240
°C	ASTM D 97	-42	-24
	g/ml cSt cSt cP cP - -	SAE J300 g/ml ASTM D 4052 cSt ASTM D 445 cSt ASTM D 445 cCP ASTM D 2983 cP ASTM D 2983 - ASTM D 2270 °C ASTM D 92	SAE J300 80W90 g/ml ASTM D 4052 0,890 cSt ASTM D 4452 14,5 cSt ASTM D 445 147 cCP ASTM D 2983 < 150.000

A safety information file is available on request.

repsol.com +34 901 111 999

Technical data sheet for Lubricants. Revision 1. March 2020.